

BAND-IT TAPE

CABLE TIES AND TIGHTENING SYSTEMS › BAND-IT

The system consists of straps and clips, which can be used to create fastenings of any shape and diameter; it is used for a wide variety of applications.

Materials available:

- W4 Stainless Steel 201
- W4 304 Stainless Steel
- W5 316 Stainless Steel
- MONEL on request, for high resistance



Mastertubi.it/q?762

Ø INTERNAL TUBE	MAXIMUM PRESSURE THAT CAN BE EXERCISED	TAPE	ROUNDS	TIGHTENINGS
12	75	3/8"	SINGLE	SINGLE
19	65	3/8"	SINGLE	DOUBLE
25	48	1/2"	SINGLE	SINGLE
38	40	1/2"	SINGLE	DOUBLE
50	35	5/8"	DOUBLE	DOUBLE
63	28	5/8"	DOUBLE	DOUBLE
76	25	5/8"	DOUBLE	DOUBLE
90	16	5/8"	DOUBLE	DOUBLE
102	14	3/4"	DOUBLE	DOUBLE
127	10	3/4"	DOUBLE	DOUBLE
150	8	3/4"	DOUBLE	DOUBLE
180	5	3/4"	DOUBLE	DOUBLE
200	2.5	3/4"	DOUBLE	DOUBLE

SERIES	APPLICATIONS	TOOLS
BAND-IT STANDARD AISI 201	Rubber hoses in general, road signs, electrical components, public service companies	

BAND-IT STANDARD AISI 304		
BAND IT AISI 316: High corrosion resistance and marine grade, acid resistant	Chemical and food industry, petrochemical, nautical	C001 (tool weight 2.0 kg)
BAND IT VALUSTRAP: Light-duty applications	Fixing of signs, fixing of insulation and caulking, packaging	
BAND IT GIANT: Heavy-duty applications	Large diameter pipes, containment of metal cable bundles	G402 (tool weight 5.3 kg)

SERIES	TAPE CODE	BANDWIDTH	TAPE THICKNESS	BREAKING LOAD	ROLL WEIGHT
		inches	mm	Kg	Kg
STANDARD AISI 201	C201	3/16□	0.38	-	0.5
	C202	1/4□	0.51	225	0.8
	C203	3/8□	0.63	400	1.6
	C204	1/2□	0.76	680	2.4
	C205	5/8□	0.76	890	3
	C206	3/4□	0.76	1090	3.6
AISI 304	C923	3/8□	0.6	340	1.6
	C924	1/2□	0.7	580	2.4
	C925	5/8□	0.7	760	3
	C926	3/4□	0.7	930	3.6
AISI 316	C403	3/8□	0.63	340	1.6
	C404	1/2□	0.76	544	2.4
	C405	5/8□	0.76	680	3
	C406	3/4□	0.76	816	3.6
VALUSTRAP AISI 304	C133	3/8□	0.4	204	1
	C134	1/2□	0.4	272	1.3
	C135	5/8□	0.4	340	1.7
	C136	3/4□	0.4	408	2
GIANT AISI 201	G430	3/4□	1.12	1500	5.4
	G431	1□	1.12	1995	6.4
	G432	1 1/4□	1.12	2495	8

