

DOUBLE-FIRED SCREW 216

CABLE TIES AND TIGHTENING SYSTEMS › TWO-WIRE CLAMP

Hose clamp for SEALING fixing of externally corrugated pipes type PU/L - PU/R -PU/P - PU/PP with high thickness and reduced pitch.

Property:

watertight and tensile connection with very low overpressure thanks to the special spiral geometry easy and quick to assemble reusable
compliant with RoHS REACH regulation

Components in W2 quality:

Clamp: stainless steel 1.4016 = AISI 430;

Cable tie wire: stainless steel 1.4310 = AISI 301 (INOX);

Screw: steel, chromed;

Body: stainless steel 1.4016 = AISI 430

Suitable for flexible hose with the following internal diameters:

32 - 38 - 40 - 45 - 50 - 55 - 60 - 65 - 70 - 75 - 80 - 90 - 100 - 102 - 110 - 115 - 120 - 120 - 125 - 127 - 130 - 140 - 150 - 152 - 160 - 175 - 180 - 200 - 225 - 250 - 250 - 300

Overpressure and underpressure are recommended operating limit values, the products can be subjected to greater loads on request. The bend radius is measured across the inside of the tube arch. We reserve the right to make technical changes. All values are determined at 20°C and are approximate data.



Mastertubi.it/q?1340