

HEAVY DOUBLE LOCK CLAMP

CABLE TIES AND TIGHTENING SYSTEMS › HEAVY CLAMP

Heavy duty bolt collars for multiple applications in AISI 430 STAINLESS STEEL.

The collar is particularly suitable for use in applications where hose clamps must meet high tightening requirements.

in particular when flexible suction and/or delivery pipes, complete with plastic or steel inserts and high Shore hardness values, need to be connected and fixed.

They are particularly suitable for use on commercial and special vehicles.

Double-locking collars are distinguished by the extremely high tension force of the tape.

The assembly of the collars is facilitated by the use of standard manual, pneumatic or electric tools.

- ☐ Breaking torque doubled
- ☐ Tripled belt tensioning Applications
- ☐ Mechanical engineering
- ☐ Agricultural machinery
- ☐ Chemical industry
- ☐ Construction machinery
- ☐ Irrigation systems
- ☐ Engine construction
- ☐ Shipbuilding
- ☐ Pumps and filters
- ☐ Railway industry
- ☐ Mining industry.

The bolt is newly designed with integrated spacer and better performance.

The W5 version is equipped with a hex socket head bolt.

Ratchets are reinforced to withstand high tightening torques

The stapling is mechanical with no welding points to eliminate the risk of contact corrosion.

Solid tape with rounded edges used to prevent injury and damage to the surface of the hose.

Salt spray corrosion resistance minimum 72 hours



Mastertubi.it/q?1145

PACKS OF 10 PIECES

SIZES AVAILABLE IN THE STANDARD VERSION IN W2 :

FIELD OF TIGHTENING	LENGTH BAND	BOLT
70-85	24mm	M8
85-100		
100-120		
120-140	26mm	M10
140-160		
160-180		
200-220		
220-240		
240-260		
260-280		
280-300		
300-325		
325-350		
350-375		
375-400		
400-425		
425-450		
450-475		
475-500		