

HEAVY DOUBLE LOCK CLAMP

CLAMPS AND TIGHTENING SYSTEMS › HEAVY CLAMP

Heavy duty bolt collars on multiple applications

The NORMACLAMP® GBS collar is particularly suitable for use in applications where hose clamps must meet high tightening requirements. In particular when flexible suction and/or delivery hoses must be connected and fixed, complete with plastic or steel inserts and high Shore hardness values. They are particularly suitable for use on commercial and special vehicles.

NORMACLAMP® GBS collars stand out for the very high tension force of the belt.

The assembly of the collars is facilitated by the use of standard manual, pneumatic or electric tools.

Benefits at a glance ☐ Double the breaking torque ☐ Triple the belt tension Applications ☐ Mechanical engineering ☐ Agricultural machinery ☐ Chemical industry ☐ Construction machinery ☐ Irrigation systems ☐ Engine construction ☐ Shipbuilding ☐ Pumps and filters ☐ Railway industry ☐ Mining industry .

Newly designed bolt with integrated spacer and better performance. The W5 version is equipped with a hexagon socket head bolt.

Reinforced pawls ☐ to withstand high tightening torques

Mechanical clinching ☐ no welding points, elimination of the risk of contact corrosion

Bridge ☐ tube protection.

Solid tape with rounded edges used to prevent injury and damage to the hose surface.

SIZES AVAILABLE IN THE STANDARD VERSION IN W2:

Resistance to corrosion in salt spray minimum 72 hours

PACKS OF 10 PIECES



Mastertubi.it/q?1145

FIELD OF TIGHTENING	LENGTH BAND	BOLT
70-85	24mm	M8
85-100		
100-120		
120-140	26mm	M10
140-160		
160-180		
200-220		
220-240		
240-260		
260-280		
280-300		
300-325		

325-350		
350-375		
375-400		
400-425		
425-450		
450-475		
475-500		