

NOZZLE WITH P15 FILTER

AUTOMOTIVE GAS EXTRACTION EQUIPMENT › GAS SUCTION VENTS

RUBBER NOZZLE FOR EXHAUST GAS EXTRACTION FROM INTERNAL COMBUSTION ENGINES WITH PREPARATION FOR P15 FILTER SYSTEM FOR FILTERING EXHAUST GASES FROM CIVIL AND COMMERCIAL VEHICLES OPERATING INSIDE STRUCTURES, WORKSHOPS.

Particle separation: >99%

Separation of aldehydes: <90%

Maximum engine displacement 4 litres

Maximum temperature: 200°C

The lifespan depends on the engine displacement, engine type, usage patterns and engine condition.

Weight: 0.4 kg

The EHC P15 filter complies with the TRGS 554 (D), COSHH (GB) and VERT (CH) B272 emission standards. The EHC particulate filter can be disposed of with normal waste.

- Straight connection cone with cap
- Double connection cone with cap
- Corner connection cone with 110° inclination
- Fitting with pneumatic sealing bellows
- Connection cone for double exhaust
- Double exhaust fitting with pneumatic sealing bellows

model	description
4060195	funnel for mufflers with external diameter 25-45mm L=165mm (for P15)
4060200	funnel for mufflers with external diameter 35-70mm L=190mm (for P15)
4060225	funnel for mufflers with external diameter 50-100mm (for P15)
4060239-2	funnel for mufflers with external diameter 75-150mm (for P15)
4060160	curved funnel for mufflers with external diameter 30-50 mm (for P15)
4060245	curved funnel for mufflers with external diameter 30-70 mm (for P15)
4060221	double funnel for mufflers with external diameter 25-45 mm (for P15)
4060220	double funnel for mufflers with external diameter 35-65 mm (for P15)
4121232	pneumatic-sealed funnel (manual inflation) for mufflers with internal Ø 37-60mm (for P15)
4121228	pneumatic-sealed funnel (manual inflation) for mufflers with internal Ø 60-85 mm (for P15)
4121177	pneumatic-sealed funnel (manual inflation) for mufflers with internal Ø 32-50mm 45° (for P15)
4121075	pneumatic-sealed funnel (manual inflation) for mufflers with internal Ø 52-80mm 45° (for P15)

