

## RUBBER NOZZLE

AUTOMOTIVE GAS EXTRACTION EQUIPMENT › GAS SUCTION VENTS

### GRN SERIES NOZZLE

conical rubber nozzle for cars and motorcycles with 160 mm diameter suction opening and hose connection sleeve equipped with a watertight manual shutter. the product is complete with probe input for the opacimetric test. Maximum temperature 200°C

Versions: Ø tube 75 - Suction cone diameter 160 mm  
Ø tube 100 - Suction cone diameter 160 mm



### GRN SERIES NOZZLE with Clip

conical rubber nozzle for cars and motorcycles with a 160 mm diameter suction opening and a hose connection sleeve equipped with a watertight manual shutter. the product is complete with a probe input for the opacimetric test. Inside there is a steel fixing clip with a protective rubber fixing terminal.  
Maximum temperature 200°C

Versions: Ø tube 75 - Suction cone diameter 160 mm  
Ø tube 100 - Suction cone diameter 160 mm



[Mastertubi.it/q?569](http://Mastertubi.it/q?569)

### GRN SERIES NOZZLE with Grip Clamp

conical rubber nozzle for cars and motorcycles with a 160 mm diameter suction opening and a hose connection sleeve equipped with a watertight manual shutter. the product is complete with a probe input for the opacimetric test. Inside there is a steel grip clip clamp with protective rubber fixing terminals. Maximum temperature 200°C

Versions: Ø tube 75 - Suction cone diameter 160 mm  
Ø tube 100 - Suction cone diameter 160 mm

### GRN SERIES NOZZLE for Commercial Vehicles

conical rubber nozzle for trucks, vans and industrial vehicles with 185 mm diameter suction opening and hose connection sleeve equipped with watertight manual shutter. Maximum temperature 200°C.

Versions: Ø tube 125 - Suction cone diameter 185 mm  
Ø tube 150 - Suction cone diameter 185 mm

On request rubber INSERT for DOUBLE OR INCLINED DRAINAGES