

GALVANIZED METALFLEX PIPE - STAINLESS STEEL

AUTOMOTIVE GAS EXTRACTION EQUIPMENT › FLEXIBLE HOSE FOR AUTO GAS

Double-interlocked flexible metal hose with polygonal section without gasket.

Available in both galvanized steel and AISI 304 stainless steel upon request.

Non-deformable profile, resistant to torsional, axial tensile and compressive loads.

On request, it can be supplied with a rubber gasket or with a double-sealed ceramic gasket for high temperatures.

Use: exhaust pipes for the delivery of hot gases derived from the combustion of cars, motorcycles, agricultural machinery, diesel generators, extraction systems, protection of electrical cables.

Upon request, it is possible to insert gaskets for special uses.

ATTENTION: the pipe has an assembly direction depending on the direction of flow

Maximum operating temperature of galvanized steel pipe 400°C

Maximum operating temperature of stainless steel pipe 700°C

available lengths - minimum drilling lot: 10 metres

Code version galvanized	Size OR mm	Weight indicative g/m	Radius curvature mm
11AVMETALZ030	30x34	800	230
11AVMETALZ035	36x40	820	230
11AVMETALZ040	41x45	940	250
11AVMETALZ045	45x50	1050	280
11AVMETALZ050	51x55	1140	305
11AVMETALZ055	56x60	1230	310
11AVMETALZ060	61x65	1550	330
11AVMETALZ065	66x70	1800	365



Mastertubi.it/q?325

11AVMETALZ070	71x75	1950	375
11AVMETALZ075	76x80	2100	385
11AVMETALZ080	81x85	2220	395
11AVMETALZ086	86x90	2350	415
11AVMETALZ090	91x95	2400	435
11AVMETALZ095	96x100	2600	450
11AVMETALZ100	101x105	2750	460
11AVMETALZ110	111x115	2940	530
11AVMETALZ115	116x120	3180	570
11AVMETALZ120	121x125	3310	605
11AVMETALZ125	126x130	3500	625
11AVMETALZ131	131x135	3720	665
11AVMETALZ141	141x145	3960	720
11AVMETALZ150	150x154	4140	805