

IP-FLEX WIRE CLIP BAND 9 W2

CABLE TIES AND TIGHTENING SYSTEMS › CLAMP RIDES THE WIRE

Clamps with worm screw and tilting drawer, which guarantee extreme versatility and speed of use, especially on large diameters. The band is full and fully serrated and the rounded edges protect Any damage to the tube. 9 mm printed tape.

W2 steel version

Tape and drawer in stainless steel 1.4016/AISI430, screw in galvanized steel Chromium VI free. Salt spray corrosion resistance minimum 144 h

W4 steel version

All components: belt, drawer, screw in stainless steel 1.4301/AISI304 Salt spray corrosion resistance minimum 240 h

- VERSION FOR PIPES WITH CLOCKWISE ROTATING SPIRAL (DX)
- VERSION FOR PIPES WITH COUNTERCLOCKWISE ROTATING SPIRAL (SX)

WHEN REQUESTING A QUOTE IT IS NECESSARY TO KNOW THE STEP OF THE SPIRAL OF THE PIPE ON WHICH THE CLAMP IS MOUNTED



CODE	scope of application	PACKAGING
41FAPNTW2-60/110_DX	60-110	10
41FAPNTW2-60/110_SX	60-110	10
41FAPNTW2-60/135_DX	60-135	10
41FAPNTW2-60/135_SX	60-135	10
41FAPNTW2-60/145_DX	60-145	10
41FAPNTW2-60/145_SX	60-145	10
41FAPNTW2-60/170_DX	60-170	10
41FAPNTW2-60/170_SX	60-170	10
41FAPNTW2-60/215_DX	60-215	10
41FAPNTW2-60/215_SX	60-215	10
41FAPNTW2-60/280_DX	60-280	10
41FAPNTW2-60/280_SX	60-280	10
41FAPNTW2-60/325_DX	60-325	10
41FAPNTW2-60/325_SX	60-325	10
41FAPNTW2-60/380_DX	60-380	10
41FAPNTW2-60/380_SX	60-380	10



Masterubi.it/q?1302