


## LOK SMC-G BSPP male metric tube

FITTINGS FOR THE CHEMICAL AND FOOD INDUSTRY › S-LOK STAINLESS STEEL FITTINGS › S-LOK FITTINGS

Straight end fitting for METRIC stainless steel pipe with BSPPT cylindrical inch thread.

Pack of 10 pieces.



UPON REQUEST, AVAILABLE IN A THERMOCOUPLE VERSION (SMCT), i.e. the S-Lok thermocouple connector HAS A THROUGH HOLE OF THE DIAMETER OF THE PIPE, the features allow the thermocouple to pass through the end of the fitting hole.

### ASSEMBLY INSTRUCTIONS:

1 - Place the length of thermocouple passed through the wire end fitting and hold it to prevent movement during assembly.

2 - Turn the 1"1/4 nut after hand tightening with a wrench, holding the body with a backup wrench for size 1/4"(6mm) or larger.



[Mastertubi.it/q?880](http://Mastertubi.it/q?880)

CODE	external tube diameter mm	BSPT inch cylindrical thread	internal hole of fitting mm
SMC 2M-2G	2	1/8	1.7
SMC 3M-2G	3	1/8	2.4
SMC 4M-4G	4	1/4	2.4
SMC 6M-2G	6	1/8	4.8
SMC 6M-4G	6	1/4	4.8
SMC 6M-6G	6	3/8	4.8
SMC 6M-8G	6	1/4	4.8
SMC 8M-2G	8	1/8	4.8
SMC 8M-4G	8	1/4	6.4

SMC 8M-6G	8	3/8	6.4
SMC 8M-8G	8	1/2	6.4
SMC 10M-2G	10	1/8	4.8
SMC 10M-4G	10	1/4	7.1
SMC 10M-6G	10	3/8	7.9
SMC 10M-8G	10	1/2	7.9
SMC 12M-4G	12	1/4	7.1
SMC 12M-6G	12	3/8	9.5
SMC 12M-8G	12	1/2	9.5
SMC 12M-12G	12	3/4	9.5
SMC 15M-8G	15	1/2	11.9
SMC 16M-4G	16	1/4	7.1
SMC 16M-6G	16	3/8	9.5
SMC 16M-8G	16	1/2	11.9
SMC 16M-12G	16	3/4	12.7
SMC 18M-8G	18	1/2	11.9
SMC 18M-12G	18	3/4	15.1
SMC 20M-8G	20	1/2	11.9
SMC 20M-12G	20	3/4	15.9
SMC 22M-12G	22	3/4	15.9
SMC 22M-16G	22	1	18.3
SMC 25M-12G	25	3/4	15.9

SMC 25M-16G	25	1	21.8
SMC 28M-16G	28	1	21.8
SMC 28M-20G	28	1-1/4	21.8
SMC 32M-20G	32	1-1/4	28.6
SMC 38M-24G	38	1-1/2	33.7