

CONDUCTIVE SOLVYKLER HOSE

HOSES › PIPES suitable for ATEX environments

Flexible EPDM rubber hose for the industrial maintenance, chemical and painting sectors in service lines used for the passage of liquid solvents such as esters and ketones, alcohol-based paints, lacquers and for its work performance with chemical products in general. Excellent resistance to aging and atmospheric conditions, light and very flexible.

Smooth antistatic black tube $R < 10^6 \text{ O/m}$ in EPDM

Textile braid inserted as reinforcement

Operating temperature $-30^\circ +100^\circ\text{C}$

Green EPDM cover, coating resistant to paint splashes, solvents and aggressive chemicals. Does not contain silicone. 40 meter rolls.



Mastertubi.it/q?441

Code item	Dimensions Ø mm	radius of curvature mm	Weight g/m
10SOLVYKLE06/13	6x13	60	0.13
10SOLVYKLE09/16	9x16	85	0.17
10SOLVYKLE08/15	8x15	70	0.16
10SOLVYKLE10/18	10x18	90	0.22
10SOLVYKLE13/21	13x21	110	0.27
10SOLVYKLE16/24	16x24	130	0.32
10SOLVYKLE20/29	20x29	150	0.44
10SOLVYKLE25/34	25x34	170	0.54