

## LOK SLS - Swivel angle male connector with SAE standard thread

PIPES AND FITTINGS FOR HYDROGEN AND FUEL CELLS › STAINLESS STEEL SAFETY CONNECTIONS › LOK D

Swivel angle male end fitting in AISI 316 stainless steel with double nose cone for pipes with external diameter in inches, SAE [American Standard] male thread whose acronym stands for Society Automotive Engineers, triangular profile with chamfered crest and bottom, internal walls they are angled at 60°.

Minimum package 10 pieces

Code	external diameter tube		fillet steak	internal hole fitting
	inches	mm	SAE	mm
SLS-4-4U	1/4"	6.35	7/16"-20	4.82
SLS-5-5U	5/16"	7.93	1/2"-20	5.84
SLS-6-6U	3/8"	9.52	9/16"-18	7.11
SLS-6-8U	3/8"	9.52	3/4"-16	7.11
SLS-8-8U	1/2"	12.70	3/4"-16	10.41
SLS-10-10U	5/8"	15.87	7/8"-14	12.70
SLS-12-12U	3/4"	19.05	1"1/16-12	15.74
SLS-14-14U	7/8"	10.22pm	1"3/16-12	18.28
SLS-16-16U	1"	25.40	1"5/16-12	10.35pm
SLS-20-20U	1"1/4	31.75	1"5/8-12	27.68
SLS-24-24U	1"1/2	38.10	1"7/8-12	34.03
SLS-32-32U	2"	50.80	2"1/2-12	45.97