

## LOK STANDARD P-SHB - NPT male hex bush reduction with NPT fe

PIPES AND FITTINGS FOR HYDROGEN AND FUEL CELLS › STAINLESS STEEL SAFETY CONNECTIONS › STAINLESS STEEL FITTINGS

| Code             | DN 1 NPT<br>male thread | DN 2 NPT<br>female thread | Length | Hole<br>Internal |
|------------------|-------------------------|---------------------------|--------|------------------|
|                  | inches                  | inches                    | mm     | mm               |
| P-SHB - 4 - 2N   | 1/4"                    | 1/8"                      | 26.7   | 7.1              |
| P-SHB - 6 - 2N   | 3/8"                    | 1/8"                      | 21.8   | 8.5              |
| P-SHB - 6 - 4N   | 3/8"                    | 1/4"                      | 30.0   | 9.6              |
| P-SHB - 8 - 2N   | 1/2"                    | 1/8"                      | 27.4   | 8.5              |
| P-SHB - 8 - 4N   | 1/2"                    | 1/4"                      | 27.4   | 11.7             |
| P-SHB - 8 - 6N   | 1/2"                    | 3/8"                      | 35.6   | 11.9             |
| P-SHB - 12 - 4N  | 3/4"                    | 1/4"                      | 27.4   | 11.4             |
| P-SHB - 12 - 6N  | 3/4"                    | 3/8"                      | 27.4   | 15.0             |
| P-SHB - 12 - 8N  | 3/4"                    | 1/2"                      | 41.4   | 15.7             |
| P-SHB - 16 - 4N  | 1"                      | 1/4"                      | 34.8   | 11.4             |
| P-SHB - 16 - 8N  | 1"                      | 1/2"                      | 34.8   | 18.5             |
| P-SHB - 16 - 12N | 1"                      | 3/4"                      | 34.8   | 22.4             |