

SPIRAL_HDPE

SPIRAL

Spiral and curved shaped flat strip in rigid shock-proof HDPE (HIGH DENSITY POLYETHYLENE).

Ideal for wrapping and containing bundles of hydraulic and electrical wiring.

Excellent resistance to LOW TEMPERATURES, abrasion, crushing, ultraviolet rays and ozone.

Excellent chemical resistance properties of the material make it particularly useful in the presence of acids, oils and aromatic solvents. Available in perforated version.

Operating temperature: -60° +100°C

SHORE hardness 66 w5 (ISO 868)

Elongation at break: 30.00 mpa

Density: 0.96 gr/cc (ISO 1183)

COLORS AVAILABLE ON REQUEST: black, yellow, green, red, blue



Mastertubi.it/q?1156

diameter internal mm	diameter external mm	weight theoretical kg/m	length roll m	step of spiral m
9	12	0.04	25	10-11
13	16	0.06	25	10-11
16	20	0.10	25	18-19
20	25	0.12	25	20-21
27	32	0.24	25	22-23
30	35	0.27	25	25-26
34	40	0.30	25	25-26
43	50	0.45	25	29-31
56	63	0.52	25	38-40
67	76	0.73	20	42-45
80	90	1.10	20	44-47
100	111	1.75	15	50-53