

FLEX / PRO SWEEPER HOSE

HOSES › Flexible rubber hoses for passage of industrial abrasives

Rubber hose for street sweepers.

Mounted externally to the side or behind the road construction machinery for conveying the material sucked from the ground to introduce it into the tank.

Tube in anti-abrasive amber-coloured natural rubber corrugated on mould.

Cover in black anti-abrasive SBR synthetic rubber corrugated with fine cloth impression, resistant to traces of oil, ozone and atmospheric agents.

Textile reinforcements and steel spiral embedded in the wall.

The hose is supplied exclusively with sleeves at the end, length and internal diameters of the sleeves upon customer request.

Operating temperature: -30° +60°C

Maximum length 6 meters.



Mastertubi.it/q?421

Diameter	Diameter	Press.	Press.	empty	radius	Weight
internal	external	of exercise	of explosion		Of curvature	
mm	mm	Cafe	Cafe	Cafe	mm	Kg/m
200	250	0.3	0.9	-0.4	100	6.3
250	300	0.3	0.9	-0.4	125	7.5
280	330	0.2	0.6	-0.4	140	8.7
300	350	0.2	0.6	-0.4	150	9.3
350	400	0.1	0.3	-0.4	180	10.6
400	450	0.1	0.3	-0.4	200	12