

TRELLVAC EXTRACTOR HD HOSE

HOSES › Flexible rubber hoses for passage of industrial abrasives

Applications: handling hose for suction of chips, sand, universal material dust, and dust, etc. Applications include hardwood, chip board, and wood veneer plants, Fiberboard plants, etc. Advantages: Light and flexible design with steel spiral.

Good bending radius. P

particularly useful when low weight and easy handling in combination with good abrasion resistance are valued.

Inside: SBR / NR wear resistant, black, smooth

Reinforcement: synthetic wire with embedded steel spiral

Cover: wear and weather resistant SBR / NR, black, corrugated

Working temperature -40° to +90° C.

Electrical properties: conductive substrate and cover, $R < 10^6 \Omega/m$.

Packaging/Packaging 12 meter rolls.

Additional information: External diameter measured at the top of the corrugation.

Technical specifications



Mastertubi.it/q?429

| Dimension Ø mm | Depression maximum Cafe | Radius of curvature mm | Weight Kg/m |
|-------------------|-------------------------------|------------------------------|----------------|
| 38x47 | 0.90 | 50 | 0.73 |
| 51x60 | 0.90 | 75 | 0.96 |
| 63x72 | 0.90 | 100 | 1.13 |
| 76x86 | 0.9 | 120 | 1.37 |
| 102x111 | 0.9 | 150 | 1.85 |
| 127x136 | 0.7 | 175 | 2.33 |
| 152x161 | 0.4 | 200 | 2.77 |

□ ϕ is subject to availability. * Length tolerance: $\pm 1\%$ (ISO 1307 Standard)