

SPIRALS IN RILSAN PA11 PHL

FITTINGS FOR COMPRESSED AIR › COMPONENTS FOR INDUSTRIAL COMPRESSED AIR PLANTS › HOSES FOR COMPRESSED AIR SYSTEMS

Spirals in RILSAN PA11 PHL

Operating temperatures: -20°C +80°C.

Useful length: 50% max 60% of the linear meters is recommended.

Colors: orange, blue, neutral, red, black, yellow, green, light blue.

The materials used comply with SAE, NF, DIN, BS, ISO standards. Designed spirals are made.

SPIRALS FOR AUTOMOTIVE BRAKING SYSTEMS ACCORDING TO DIN 73378 - 74324 STANDARDS

Code	Dimensions tube mm	Length tube m	TO rest m	Usage maximum m	Pressure of exercise at 23°C Cafa
01SR0D0002/04	2x4	10	0.40	6.50	44
01SR0D02.5/04	2.5x4	10	0.40	6.50	30
01SR0A0004/06	4x6	30	0.95	20	26
01SR0A0006/08	6x8	30	1.00	20	19
01SR0A0008/10	8x10	30	1.00	20	14
01SR0A0010/12	10x12	30	1.00	20	12
01SR0A0012/15	12x15	30	0.92	20	14
01SR0A0014/18	14x18	30	0.97	20	16
01SR0A0015/18	15x18	30	0.97	20	12
01SR0A0018/22	18x22	60	0.98	40	13
01SR0A0020/24	20x24	50	0.98	35	12
01SR000025/30	25x30	50	1.00	30	10



Mastertubi.it/q?396