

PA12 PIPE FOR SELF-EXTINGUISHING AIR SYSTEMS

FITTINGS FOR COMPRESSED AIR › COMPONENTS FOR INDUSTRIAL COMPRESSED AIR PLANTS › HOSES FOR COMPRESSED AIR SYSTEMS

Flexible linear tube in **POLYAMIDE PA 12** of chemical origin,
SELF-EXTINGUISHING ACCORDING TO UL94 V2 STANDARDS,
halogen-free.

Industrial applications:

automation, fixed compressed air systems in factories and workshops.

Available colors: light blue

Operating temperature: -30°C to +70°C

Available upon request in 100-meter rolls or 4-meter bars.

Packaging: standard polyethylene film or in cardboard boxes or wooden spools.



Image: RILSAN-IN-BARRE.jpg



Mastertubi.it/q?402

PRESSURE TABLE AS A FUNCTION OF TEMPERATURES: 20°
30° 40° 50° 60°

CODE	Diameter inside-outside mm	Radius of curvature mm	Pressure of exercise bar	Pressure of explosion bar
03PA11AU02,7/06	2.7x4	25	28	85
03PA11AU04/06	4x6	35	29	88
03PA11AU06/08	6x8	40	21	63
03PA11AU08/10	8x10	60	16	49
03PA11AU10/12	10x12	85	13	40
03PA11AU12/15	12x15	90	16	49
03PA11AU12,5/15	12.5x15	100	13	40
03PA11AU15/18	15x18	140	13	40
03PA11AU18/22	18x22	200	15	44
03PA11AU20/24	12x15	300	13	40
03PA11AU24/28	24x28	350	11	34

03PA11AU25/30	25x30	400	13	40
03PA11AU34/40	34x40	500	12	36