

HOSE 12 HR type 0 - HIGH RESISTANCE

HOSES › Hoses for Pneumatic Applications › POLYAMIDE TUBES - RILSAN PA11 - PA12

Flexible linear tube in **POLYAMIDE 12** of chemical origin.

PHL (light-stable and plasticized) according to DIN 73378/74324

Industrial applications: LUBRICATION, NEBULIZATION

Available colors: BLACK, NEUTRAL

Operating temperature: -40°C to +80°C



Mastertubi.it/q?1250

Diameter internal mm	Diameter external mm	Thickness mm	Minimum radius of curvature mm	Minimum operating pressure Cafe	Colors available
0.50	1.10	0.300	5	105	neutral
0.60	1.15	0.275	5	88	neutral
1.10	1.90	0.400	10	74	neutral
2.30	4.00	0.850	20	75	neutral-red
2.50	4.00	0.750	20	64	neutral-black
3.00	6.00	1,500	20	93	neutral-black red
3.60	6.35	1,375	30	77	neutral-black
4.00	6.00	1,000	35	56	neutral-black
5.00	8.00	1,500	40	64	neutral-black
5.00	9.52	2,260	35	87	black-silver
6.00	8.00	1,000	65	40	neutral-black
6.00	10.00	2,000	45	70	black
7.00	12.70	2,850	50	81	black
8.00	10.00	1,000	100	31	black-neutral
10.00	12.00	1,000	150	25	neutral