

## TRIPLE LAYER FIREPROOF NON-SPARKING POLYURETHANE HOSE

HOSES › Hoses for Pneumatic Applications › POLYAMIDE TUBES - RILSAN PA11 - PA12

Triple-layer, flexible, spark-proof linear hose made of plasticized Polyamide 12 PHL, stabilized against light and heat. Internally reinforced with a tightly woven PBT braid. Externally, with an additional layer of anti-abrasive 85 shA polyurethane, self-extinguishing to UL94 V0 standards, suitable for improving protection against sparks and welding

spatter. The anti-abrasive outer sheath (64 shore D hardness) can be easily removed with a special tool because it is not

glued, facilitating assembly operations. Hose suitable for use with quick-connect fittings.

Black color, 100 meter rolls



[Mastertubi.it/q?399](http://Mastertubi.it/q?399)

| Diameter tube mm | Weight gr/m | Radius of curvature mm | Operating pressure Bar |
|------------------|-------------|------------------------|------------------------|
| 2.5x4            | 33.8        | 15                     | 30                     |
| 4x6              | 52.2        | 30                     | 26                     |
| 6x8              | 68.6        | 50                     | 19                     |
| 5x10             | 91.4        | 60                     | 19                     |
| 9x12             | 117.1       | 75                     | 19                     |