

## FGR NORMACONNECT FLEX E REPAIR COLLARS

CABLE TIES AND TIGHTENING SYSTEMS › REPAIR COLLARS

### NORMACONNECT® GRIP E

Robust couplings for rigid pipes, equipped with an anchoring ring with conical teeth.

Used to connect metal pipes.

The anchor ring with conical teeth cuts into the surface of the tube (steel, stainless steel or cast iron) and ensures a safe and robust axial locking.

Thanks to its special design, the joint is able to withstand even high vibratory loads.

Maximum operating pressure 16 bar

The progressive locking effect ensures a trouble-free and maintenance-free connection.

- Space-saving connector
- Withstands high vibration loads
- Shock resistant
- Reusable

□ Sizes: 26.9mm □ 812.8mm

□ Material: AISI 304, AISI 316 (W2 - W4 - W5)

□ EPDM: Sizes from 26.9 mm to 168.3 mm: -30°C +125°C

Sizes over 180.0 mm: -20°C +80°C

□ NBR: from -20°C up to +80°C

□ FKM: -10°C to +150°C

TECHNICAL DATA SHEETS AND ORDER CODES:

<https://www.norma-connects.com/en/products/norma-fgr-grip>



[Mastertubi.it/q?1628](https://www.mastertubi.it/q?1628)