

ARMORVIN TOTAL PU OIL TPHF HOSE

HOSES › Flexible hoses for liquids suitable for food use › TUBES FOR EXTRA VIRGIN OLIVE OIL

TPHF Polyurethane tube with embedded galvanized steel spiral

Use: for delivery and suction of liquids, oils and fatty food substances

Smooth surface both internally and externally.



Operating temperature: -25°C 90°C

Without Orto Phthalates PHF

Phthalate Free TPHF



Mastertubi.it/q?1185

Certifications:

- Declaration of Conformity - EU
- Declaration of Conformity - FDA
- Communication of presence of SVHC substances
- RoHS Declaration
- Conflict Minerals Statement
- USA TSCA Statement

section tube mm	Nominal Ø inch	External Ø mm	Exercise depression at 23° m/H ₂ O	Operating pressure at 23° bar	Burst pressure at 23° bar	Curvature radius mm	Weight meter g	Roll length m
10	3/8	16.2	9	7	21	40	180	30
12		18.2	9	7	21	48	190	30
16	5/8	22.2	9	7	21	74	260	30
18		25	9	7	21	76	350	30
19	3/4	26.2	9	7	21	80	410	30
20		28.5	9	7	21	80	410	30
25	1	33.5	9	7	21	100	520	30
30		39.2	9	7	21	120	620	30
32	1 1/4	41	8	6	18	130	690	30
35		43.6	8	6	18	135	750	30
38	1 1/2	46.7	8	6	18	140	800	30
40		49.4	8	6	18	160	900	30

45	1 3/4	54	8	6	18	180	1040	30
50	2	60.4	8	6	18	200	1160	30
60		70	8	6	18	240	1440	30
63	2 1/2	73.4	8	5	15	280	1560	30
70		80	8	5	15	300	1650	30
75		85.2	7	5	15	320	1730	30
76	3	86	7	5	15	330	1750	30
80		90	7	4	12	340	1800	30
100		114	7	3	9	400	3250	20
102	4	116	7	3	9	420	3300	20