

## ASTM C-542 FOREST FIRE HOSE

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › FIRE-FIGHTING ITEMS › HOSES FOR FOREST FIRE FIGHTING

Fire hose that can be rolled up on a reel, robust and flexible, resistant to abrasion and fire-fighting foams.

**Standards: ASTM C-542**

**Application: cord hose for delivering water and fire-fighting liquids, which can be rolled up on a reel, robust and flexible, designed for service on fire engines.**

Temperature: -20°C to +70°C.

Marking: "IVG FIRE" embossed tape.










Tube : black, smooth, synthetic rubber resistant to chemicals and firefighting foams.

Reinforcement : high resistance synthetic fabrics.

Cover : black, smooth (wrapped finish), CR NON-FLAME PROPAGATING rubber, resistant to atmospheric agents, abrasion and oils.



Mastertubi.it/q?1292

Code	Diameter		Pressure Work		Pressure I explode		Weight	radius	Length
	Internal	External	Cafe	psi	Cafe	psi	kg/m	mm	Maximum
									
	mm	mm	Cafe	psi	Cafe	psi	kg/m	mm	m
1393820	12	18	40	600	120	1800	0.21	200	120
1404164	13	21	40	600	120	1800	0.27	220	120
1409581	19	30	40	600	120	1800	0.53	240	120
1410652	25	37	40	600	120	1800	0.70	260	120