

OUTDOOR WALL HYDRANT

*FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › FIRE-FIGHTING ITEMS › WALL HYDRANTS CE
UNI EN 671/2:2003*

OUTDOOR WALL HYDRANT Art. CE40 - DN 45 compliant with UNI EN 671/2 - CE marked, 0497/CPR/134

Form ☐ C ☐ type 2, complete with:

- ☐ Outdoor box in galvanized steel painted red RAL 3000 based on polyester resins, resistant to corrosion in accordance with ISO 9227, with sloping roof, easy-opening handle with the possibility of sealing, ventilation slots and hole for the passage of the supply hose.
- ☐ Painted sheet metal door with identification symbol.
- ☐ DN45 flexible hose certified EN 14540, with UNI 804 fittings and UNI 7422 binding with rubber binding cover sleeves.
- ☐ Hose protection harness in red plastic material.
- ☐ 1 $\frac{1}{2}$ hydrant tap with thread compliant with ISO 7-1.
- ☐ Jet regulation lance.
- ☐ Assembly and use instructions.
- ☐ CE mark identification code sticker.
- ☐ On request: white RAL 9016

roll of: 15-20-25-30 metres



Mastertubi.it/q?746