

## CONNECTED RED FIRE HOSE

*FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › FIRE-FIGHTING ITEMS › FIRE-FIGHTING UNI CONNECTED HOSES*

FLATABLE RED TUBE IN HIGH TENACITY POLYESTER FABRIC WITH A WATERPROOFING UNDERLAY.

EXTERNAL COVERING IN RED RESIN IS HIGHLY RESISTANT TO ABRASION, BACTERIAL ATTACK AND MANY CHEMICAL, ATMOSPHERIC AGENTS AND OZONE. SUITABLE FOR HEAVY DUTY USE

- UNI 804 FITTING
- BINDING ACCORDING TO UNI 7422 STANDARD WITH RUBBER SLEEVE COVER BINDING COVER
- DIAMETER 45mm COMPLIANT WITH EN 14540 STANDARDS
- DIAMETER 70mm ACCORDING TO UNI 9487 MI CERTIFIED

AVAILABLE DIAMETERS: DN25 - DN45 - DN70

ROLLS OF: 10m - 15m - 20m - 25m - 30m - 40m - 50m - 60m

POSSIBILITY OF PVC OR EPDM RUBBER UNDERLAYER



[Mastertubi.it/q?741](http://Mastertubi.it/q?741)