

## CAMLOCK TYPE C

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › CAM LOCK FITTINGS

This type of fitting has been designed for quick and safe joining in the shortest time possible between two pipes.


By inserting the male version inside the female version you will quickly have a full bore mechanical coupling with tightening via two lateral levers, the whose eccentric on the fulcrum will obtain the definitive locking, through a pin or a system spring you get the safety stop of the two fins.

The seal is guaranteed by standard NBR rubber gaskets or, in the case of fittings, by in PP the gasket is in EPDM.

Complies with Military Regulation AA-59326A.

Also available on request in the stainless steel version EN14420-7 (DIN) 16bar on all DN's including flat gasket in NBR.

**Available materials:** AISI316, BRASS, ALUMINUM, POLYPROPYLENE



Mastertubi.it/q?56

DIAMETER NOMINAL	DN	DIAMETER RUBBER HOLDER mm	PRESSURE SS AISI 316 BAR	PRESSURE BRASS BAR	PRESSURE ALUMINUM BAR	PRESSURE POLYPROPYLENE BAR
DN015	1/2"	13	10	10	10	8.5
DN020	3/4"	13	-	-	-	8.5
DN020	3/4"	21	17	17	17	8.5
DN025	1"	27	17	17	17	8.5
DN032	1"1/4	34	17	17	17	6.5
DN040	1"1/2	34	-	-	-	6.5
DN040	1"1/2	40	17	17	17	6.5
DN050	2"	27	-	-	-	6.5
DN050	2"	40	17	-	-	6.5
DN050	2"	51	17	17	17	6.5
DN065	2"1/2	40	10	10	10	-
DN080	3"	76	8.5	8.5	8.5	5

DN100	4"	103	6.5	6.5	6.5	5
DN125	5"	128	5	5	5	-
DN150	6"	152	5	5	5	-
DN200	8"	200	-	-	4	-