


## CAMLOCK TYPE E

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › CAM LOCK FITTINGS



This type of fitting has been designed for the quick and safe connection between two pipes in the shortest possible time. By inserting the male version inside the female version you will quickly have a full passage mechanical coupling with the tightening using two lateral levers, whose eccentric on the fulcrum will obtain the definitive locking, using a pin or a spring system the locking stop is obtained safety of the two flaps. Including flat PTFE gasket.

In compliance with Military regulation AA-59326A.



Mastertubi.it/q?58

**Available MATERIALS:** STEEL AISI316, BRASS, ALUMINUM, POLYPROPYLENE, conductive polypropylene <math>10^8 \Omega</math>

DIAMETER NOMINAL	DIAMETER HOSE HOLDER mm	PRESSURE AISI AISI316 BAR	PRESSURE BRASS BAR	PRESSURE ALUMINUM BAR	PRESSURE POLYPROPYLENE BAR
DN015	13	10	10	10	-
DN020	13	-	-	-	8.5
DN020	21	17	17	17	8.5
DN025	27	17	17	17	8.5
DN032	34	17	17	17	6.5
DN040	34	-	-	-	6.5
DN040	40	17	17	17	6.5
DN050	27	-	-	-	6.5
DN050	40	17	-	-	6.5
DN050	51	17	17	17	6.5
DN065	64	10	10	10	-

DN080	76	8.5	8.5	8.5	5
DN100	103	6.5	6.5	6.5	5
DN125	128	5	5	5	-
DN150	152	-	-	5	-
DN200	200	-	-	4	-