

## CAMLOCK TYPE F


FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › CAM LOCK FITTINGS

This type of fitting has been designed for quick and safe joining in the shortest possible time between two pipes. By inserting the MALE version inside the female version you will have quickly a full passage mechanical coupling with tightening using two levers laterals, whose eccentric on the fulcrum will obtain definitive locking, via a pin or a system the safety stop of the two flaps is obtained by means of a spring. The seal is guaranteed by gaskets

standard in NBR rubber or in different material depending on the fluid passing through.

The ends of the fittings can be supplied threaded, flanged for welding or hose holder.

In compliance with Military regulation AA-59326A



**Available MATERIALS :** AISI316 STEEL, BRASS, ALUMINUM, POLYPROPYLENE

**THREAD :** BSPT/NF ISO 228-1 also in NPT version on request

	THREADED BSP	PRESSURE AISI 316 BAR	PRESSURE BRASS BAR	PRESSURE ALUMINUM BAR	PRESSURE PP BAR	THREADED NPT
DN015	1/2"	10	10	10	8.5	-
DN020	1/2"	-	-	-	8.5	-
DN020	3/4"	17	17	17	8.5	-
DN025	1"	17	17	17	8.5	X
DN032	1"1/4	17	17	17	6.5	X
DN040	1"1/4	-	-	-	6.5	-
DN040	1"1/2	17	17	17	6.5	X
DN050	2"	17	17	17	6.5	X
DN065	2"1/2	10	10	10	-	X
DN080	3"	8.5	8.5	8.5	5	X
DN100	4"	6.5	6.5	6.5	5	X
DN125	5"	5	5	5	-	X
DN150	6"	5	5	5	-	X
DN200	8"	-	-	4	-	-



[Mastertubi.it/q?59](http://Mastertubi.it/q?59)