

ONE-WAY CYLINDRICAL VALVE OT PN20

FITTINGS FOR COMPRESSED AIR › FITTINGS AND CONNECTIONS FOR PNEUMATIC SYSTEMS › Accessories, mini valves, silencers

CHARACTERISTICS:

Body: OT 58 yellow brass

Shutter: OT 58 yellow brass

Spring: AISI 302 stainless steel

O-ring: - NBR operating temperature from -20°C to 100°C

- VITON from -20°C to 205°C on request

- EPDM: from -40°C to 130°C on request

Possibility of assembly with VITON or EPDM O-rings - Different opening pressures on request -

Possibility of supplying them degreased

Also available on request with NPT thread

Clamping ring: AISI 302 stainless steel

THREAD Cylindrical gas BSPP UNI ISO 228/1 from G1/8" to G1"

WORKING PRESSURE: 20 Bar

Indication of the direction of the fluid engraved on the body



Mastertubi.it/q?1183

USE: Compressed air, water, gas, non-aggressive mineral or synthetic oils in non-corrosive environments and fluids compatible with the construction materials.

Measure	Length mm	Height mm	Weight gr.	Minimum pressure of opening Cafe
1/8"	40	17	52	0.35
1/4"	41	17	45	0.30
3/8"	47	22	90	0.25
1/2"	56	27	153	0.08
3/4"	66	34	285	0.10
1"	79	40	388	0.80