

## POLYURETHANE SEWAGE HOSE

HOSES › Water intake hoses

**PVC hose internally coated with anti-abrasive TPU and reinforcement spiral in shock-proof rigid PVC .**

Its robust structure, together with the polyurethane layer, is particularly suitable for use in harsh and highly abrasive conditions.

The antistatic version (available on request) is produced with brass-plated steel wire inserted into the plastic wall to respond even better to the needs of abrasion resistance even on the outside.

Wavy gray outer cover, smooth red interior. Operating temperature: -25°C +60°C.



[Mastertubi.it/q?1062](http://Mastertubi.it/q?1062)

**FIELDS OF APPLICATION:** construction, industry in general, for suction and delivery of abrasive liquids (sludge, sand, cement, grit, gravel).

Diameter hole internal mm	Weight g/m	Pressure of exercise Cafe	Pressure of explosion Cafe	Depression mH <sub>2</sub> O	radius of curvature mm	Roll m
38	680	5	15	10	155	50
40	710	5	15	10	160	50
45	830	4	12	9	180	50
50	980	4	12	9	200	50
60	1230	4	12	9	200	50
63.5	1360	4	12	9	240	50
70	1570	4	9	9	280	50
76	1690	3	9	9	310	50
80	1790	3	9	9	320	50
90	2090	3	9	9	360	30
102	2700	3	9	8.5	410	30
110	2930	3	9	8.5	450	30

120	3270	2.5	7.5	8	480	30
127	3510	2.5	7.5	8	510	30
152	4730	2	6	8	610	20