

WATER VACUUM HOSE

HOSES › Water intake hoses

Rubber hose for suction and delivery of water and non-corrosive fluids.

Tube: black synthetic rubber. High tenacity canvases inserted.

Built-in steel spiral. Anti-abrasive cover with fine cloth finish, resistant to atmospheric agents, black colour.

Maximum operating pressure: 10 bar, burst 30 bar.

Suction value: 0.8 bar

Operating temperature: -30° +80° C.

Rolls from 40 to 61 metres.



Mastertubi.it/q?278

Code	Diameters mm	Weight Kg/m	radius of curvature mm
04GASP1000019 T	19x29	0.55	115
04GASP1000025 T	25x35	0.77	150
04GASP1000030 T	30x40	0.91	180
04GASP1000032 T	32x42	0.97	190
04GASP1000035 T	35x45	1.08	210
04GASP1000038 T	38x49	1.20	230
04GASP1000040 T	40x51	1.28	240
04GASP1000045 T	45x57	1.49	270
04GASP1000050 T	51x62	1.76	310
04GASP1000055 T	55x67	1.85	350
04GASP1000060 T	60x72	1.93	360
04GASP1000060 T	63.5x76	2.40	380
04GASP1000070 T	70x84	2.65	420
04GASP1000075 T	75x88	2.85	460
04GASP1000080 T	80x92	3.09	480
04GASP1000090 T	90x102	3.20	540
04GASP1000102 T	102x117	4.00	610
04GASP1000110 T	110x123	4.66	660

04GASP1000120 T	120x137	5.21	720
04GASP1000127 T	127x144	7.00	760
04GASP1000150 T	152x170	10.00	920
04GASP1000203 T	203x228	5.00pm	1220