

SEWAGE SUCTION HOSE

HOSES › Water intake hoses

Rubber hose for suction and delivery of water and non-corrosive fluids.

Tube: black synthetic rubber.

High tenacity canvases inserted.

Built-in steel spiral.

Wavy external surface with canvas impression.


Anti-abrasive cover with fine cloth finish, resistant to atmospheric agents.

With smooth end sleeves at the ends.

Suction value: 0.8 bar

Operating temperature: -30°C to +80°C.

Applications: water pipes for agricultural irrigation systems, construction, civil protection and fire prevention, tankers, agricultural trailers, pumps, draining of septic tanks.



Mastertubi.it/q?279

Available packages: 2/3/4/5/6 meter BARS

Code	Dimensions OR mm	pressure of exercise Cafe	Weight Kg/m	Radius of curvature mm
04GLIQ0000051	51	10	1.60	250
04GLIQ0000060	60	10	1.80	300
04GLIQ0000076	76	10	2.45	380
04GLIQ0000080	80	10	2.77	400
04GLIQ0000100	102	10	3.40	500
04GLIQ0000110	110	10	3.82	550
04GLIQ0000120	120	10	4.36	600
04GLIQ0000127	127	5	4.50	635
04GLIQ0000133	133	5	4.70	665
04GLIQ0000150	152	5	5.60	750
04GLIQ0000203	203	5	9.60	1015
04GLIQ0000254	254	3	12.25	1270
04GLIQ0000305	305	3	16.60	1125