

ARIZONA SUPERELASTIC TUBE

HOSES › Water intake hoses

Very flexible general purpose plastic hose for medium to heavy duty.

Very robust with external shock-proof rigid PVC spiral.

Completely smooth internal surface, smooth external surface.

High suction resistance. SHORE A hardness 57

Resistant to the action of atmospheric agents and most chemical products.


Operating temperature: -25°C +55°C

Vacuum value: 9 meters of water column.

Suitable for heavy-duty uses where extreme flexibility is required.

Ideal for industrial liquid suction, irrigation, well draining, waste water purging.

COLOR: gray with green reinforcement spiral



Mastertubi.it/q?981

Item	Dimension Ø inch	Dimension Ø mm	Weight gr/m	Curvature radius mm	Operating pressure bar	Rolls m
04PARI0000025	1"	25	500	100	7	50
04PARI0000032	1 1/4"	32	600	130	6	50
04PARI0000038	1 1/2"	38	700	150	6	50
04PARI0000040		40	740	160	6	50
04PARI0000045	1 3/4"	45	900	180	5.5	50
04PARI0000050	2"	50	1050	200	5	50
04PARI0000060		60	1250	240	4.5	50
04PARI0000063	2 1/2"	63	1390	250	4.5	50
04PARI0000075		75	1700	300	4	30
04PARI0000076	3"	76	1700	300	4	30
04PARI0000080		80	1850	320	3.5	30
04PARI0000089	3 1/2"	89	2250	360	3.5	30
04PARI0000090		90	2250	360	3.5	30
04PARI0000100		100	2700	400	3	30
04PARI0000102	4"	102	2700	400	3	30
04PARI0000110		110	3100	440	3	20
04PARI0000120		120	3600	480	2.5	20
04PARI0000125		125	3900	500	2.5	20
04PARI0000127	5"	127	3900	500	2.5	20
04PARI0000130		130	4100	520	2.5	20
04PARI0000150		150	4200	600	2	20

04PARI0000152	6"	152	5000	610	2	20
04PARI0000160		160	5600	640	2	20
04PARI0000200		200	9500	800	1.5	-
04PARI0000203	8"	203	9500	800	1.5	-
04PARI0000254	10"	254	13500	1000	1.5	-
04PARI0000304	12"	304	18000	1200	1.5	-