

LOUISIANA TUBE

HOSES › Water intake hoses

Flexible PVC hose with rigid shock-proof and crush-proof PVC reinforcement spiral.

Resistant to atmospheric agents and most chemical products.

Smooth internal surface.

Good resistance in suction and delivery.

Suitable for contact with food according to DDC.

Operating temperature: -15°C +60°C Yellow colour, transparent with ivory spiral.

Code	Dimensions mm	Weight g/m	radius of curvature mm	Pressure maximum bar	Rolls m
04PLUI0000020	20x26,2	275	75	8	50
04PLUI0000025	25x31,6	330	120	8	50
04PLUI0000030	30x37,0	420	140	7	50
04PLUI0000032	32x39,2	460	150	7	50
04PLUI0000035	35x41,8	500	160	7	50
04PLUI0000038	38x45,4	550	170	6.5	50
04PLUI0000040	40x47,6	610	180	6.5	50
04PLUI0000045	45x52,8	670	200	6.5	50
04PLUI0000050	50x58,2	810	220	6	50
04PLUI0000060	60x69,0	970	270	5	50
04PLUI0000063	63x71,5	1040	290	5	50
04PLUI0000070	70x79,2	1200	320	4	50
04PLUI0000075	75x85,4	1380	350	4	50
04PLUI0000080	80x90,6	1560	360	4	25
04PLUI0000090	90x100,4	1800	430	4	25
04PLUI0000100	100x112,0	2160	480	4	25
04PLUI0000102	102x114,0	2160	480	4	25
04PLUI0000110	110x122,0	2400	530	4	25
04PLUI0000120	120x132,4	2800	680	3	25
04PLUI0000125	125x137,6	3130	730	3	25
04PLUI0000150	150x164,4	4250	810	3	25
04PLUI0000200	200x218,2	6400	900	2	10