

PVC SEWAGE HOSE

HOSES › Hydrocarbon suction hoses

Very flexible general purpose plastic hose for medium to heavy duty.

Very robust with external shock-proof rigid PVC spiral. Completely smooth internal surface, smooth external surface. High suction resistance.

Resistant to the action of atmospheric agents and most chemical products.

Operating temperature: -25°C +60°C

Vacuum value: 9 meters of water column.

Suitable for heavy-duty uses where extreme flexibility is required, ideal for industrial liquid suction, irrigation, well purging, waste water purging.

COLOR: gray with blue spiral.



Mastertubi.it/q?280

Item number	Dimension Ø mm	Weight gr/m	Curvature radius mm	Operating pressure bar	Rolls m
04PLIQ0000025	25	500	100	7	50
04PLIQ0000032	32	600	130	6	50
04PLIQ0000038	38	700	150	6	50
04PLIQ0000040	40	800	160	6	50
04PLIQ0000045	45	900	180	5.5	50
04PLIQ0000050	50	1050	200	5	50
04PLIQ0000060	60	1250	240	4.5	50
04PLIQ0000063	63	1390	240	4.5	50
04PLIQ0000070	70	1550	280	4	50
04PLIQ0000076	76	1700	300	4	50

04PLIQ0000080	80	1850	320	3.5	30
04PLIQ0000090	90	2250	360	3.5	30
04PLIQ0000102	102	2700	400	3	30
04PLIQ0000110	110	3100	440	3	30
04PLIQ0000120	120	3600	480	2.5	20
04PLIQ0000125	125	3900	510	2.5	20
04PLIQ0000130	130	4100	520	2.5	20
04PLIQ0000152	152	5000	610	2	20
04PLIQ0000160	160	5600	640	2	20
04PLIQ0000200	200*	10000	800	1.5	10

(*) DN 200 - SUPPLIED ONLY IN FLEXIBLE RODS 10 METERS LONG.