

WATER WAVY HOSE

HOSES › Flexible hoses for liquid suction for industrial, agricultural and sewage disposal

Rubber hose for suction and delivery of water and non-corrosive fluids.

Tube: black synthetic rubber.

High tenacity canvases inserted.

Built-in steel spiral.

Wavy external surface with canvas impression.

Anti-abrasive cover with fine cloth finish, resistant to atmospheric agents.

Smooth end sleeves at the ends.

Maximum operating pressure: 10 bar, burst 30 bar.

Maximum suction value: 0.8 bar

Operating temperature: -30°C to +80°C.

Applications: water pipes for agricultural irrigation systems, construction, civil protection and fire prevention, tankers, agricultural trailers, water pumps, liquid fertilizers, septic tank clearing.

SIZES ON REQUEST.



Mastertubi.it/q?283

Item number	Dimensions Ø mm	Weight Kg/m	Curvature radius mm	Maximum operating pressure bar	Burst pressure bar	Bar suction
04OND0000050	50	1.6	250	10	30	0.8
04OND0000060	60	1.8	300	10	30	0.8
04OND0000080	80	2.8	400	10	30	0.8
04OND0000100	102	3.4	500	10	30	0.8
04OND0000120	120	4.4	600	10	30	0.8
04OND0000152	152	5.6	750	5	15	0.8
04OND0000203	203	9.6	1015	5	15	0.8
04OND0000254	254	12.3	1270	3	9	0.7
04OND0000305	305	16.6	1525	3	9	0.7