

BLEED TRUCK/5/CLC

HOSES › FLEXIBLE HOSES FOR LIQUID SUCTION, WELL CLEANING, AGRICULTURE

Rubber hose for suction and delivery of water and non-corrosive fluids.

Tube: Heavy abrasion resistant black synthetic rubber.
High tenacity canvases inserted. Built-in steel spiral.
External surface with wide corrugation and canvas impression.



Mastertubi.it/q?843

Anti-abrasive covering with fine cloth impression and wide corrugation, resistant to atmospheric agents. Smooth end sleeves at the ends on request.

Maximum working pressure 5 bar, burst 15 bar.

Maximum suction value: 0.8 bar at room temperature

Operating temperature: -30°C to +90°C.

Applications: water pipes for agricultural irrigation systems, construction, civil protection and fire prevention, tankers, agricultural trailers, water pumps, liquid fertilizers, septic tank clearing.

Packed in rolls or standard bars maximum 4 meters - other sizes on request.

Diameter internal mm	Weight Kg/m	radius of curvature mm	Max pressure of exercise Cafe	Pressure of explosion Cafe	Aspiration Cafe
50	1.6	175	5	15	0.8
60	1.8	210	5	15	0.8
80	2.8	280	5	15	0.8
102	3.4	357	5	15	0.8
120	4.4	420	5	15	0.8
152	5,6	532	5	15	0.8
203	9.6	710	5	15	0.8
254	12.3	889	3	9	0.7
305	16.6	1067	3	9	0.7