

SAE J30R7 L/L BIOFUEL PIPE

HOSES › Hydrocarbon delivery hoses

Delivery hose for mineral oils, E5 and E10 petrol, diesel and BIO DIESEL fuels type B10, B20, B30, HVO

Maximum temperature 100°C.

Inner tube: Black, smooth **NBR rubber**.

Cover: Black, smooth **NBR rubber**, resistant to temperature, oils and atmospheric agents.

Operating temperature -40°C +125°C

COMPLIANCE WITH SAE J30R7 STANDARDS

certification that guarantees excellent resistance to fuels with high ethane concentrations, biodiesel in extreme temperatures.

Low permeability tube (550 g/ m² /day). Permeability test, 8 days in fuel C at room temperature.

reduces fuel vapor emissions, helping to comply with environmental regulations.

The high-quality materials used ensure long life with reliable performance.

Used in fuel supply systems in motor vehicles (cars, industrial vehicles, earth-moving machines, tractors, motorcycles).



Mastertubi.it/q?1607

Diameter internal	Diameter external	Weight	Pressure Of exercise	Pressure Of explosion	Radius Of curvature	rolls
mm	mm	kg/m	bar	bar	mm	m
5	11	0.12	10	30	35	25
6	12.3	0.13	10	30	45	25
8	14.3	0.20	10	30	75	25
10	17.2	0.23	10	30	85	25
13	20.2	0.27	10	30	95	25