

SAE J30R9 L/L BIOFUEL PIPE

HOSES › Hydrocarbon delivery hoses

Pipe suitable for fuel injection lines, diesel, biodiesel (B10, B20, B100, RME); petrol E10, E15, E85.

Operating temperature -40°C +135°C peaks 150°C

Underlayer: Black, smooth rubber Black **FKM** .

Aramid fiber braided reinforcement

Cover: Smooth black **ECO** rubber, resistant to temperature, oils and ozone

COMPLIANCE with SAE J30R9 Standards, conductive tube according to EN ISO8031-DEC2009, R= 1MO/mAE

certification that guarantees excellent resistance to fuels with high ethane concentrations, biodiesel in extreme temperatures.

Low permeability tube (550 g/ m² /day). Permeability test, 8 days in fuel C at room temperature.

reduces fuel vapor emissions, helping to comply with environmental regulations.

The high-quality materials used ensure long life with reliable performance.

Used in fuel supply systems in motor vehicles (cars, industrial vehicles, earth-moving machines, tractors, motorcycles).



Mastertubi.it/q?1608

Diameter internal	Diameter external	Weight	Pressure of work	Burst pressure	Radius of curvature	Rolls
mm	mm	kg/m	bar	bar	mm	m
5	11	0.10	12.5	62	60	25
6	12	0.13	12.5	62	70	25
8	15	0.16	12.5	62	80	25
10	17.2	0.21	10	34	85	25
13	20.2	0.28	10	34	100	25