

RUBBER HOSE BI.BLUE/60 DIELECTRIC

HOSES › Hot water hoses

Dielectric EPDM rubber hose with textile inserts. Blue canvas finish cover.

Non-conductive white interior. ALSO CALLED PIEDMONT TUBE.

Applications: hose particularly suitable for induction furnaces, steelworks, glassworks, for delivering pressurized water and low-concentration acid and alkaline solutions

Operating temperature: -40°C to +100°C peaks of 120°C.

Dielectric strength >5000 V/mm.

Safety coefficient three for burst pressure.



Code	Dimensions Ø mm	Curvature radius mm	Working pressure bar	Theoretical weight Kg/m
10GBIBLU6009/16	9x16	50	25	0.21
10GBIBLU6012/21	12x21	70	20	0.29
10GBIBLU6015/23	15x23	90	20	0.37
10GBIBLU6015/25	15x25	120	20	0.43
10GBIBLU6019/30	19x30	120	20	0.52
10GBIBLU6022/30	22x30	180	15	0.40
10GBIBLU6025/34	25x34	200	15	0.50
10GBIBLU6030/42	30x42	240	15	0.82
10GBIBLU6038/52	38x52	280	20	1.10
10GBIBLU6040/54	40x54	300	20	1.20
10GBIBLU6045/60	45x60	340	15	1.45
10GBIBLU6050/68	50x68	330	15	2.00
10GBIBLU6060/78	60x78	480	15	2.40



Master