

RADIATOR RUBBER HOSE

HOSES › Specific flexible hoses for engine test rooms

Pipe passing hot water mixed with antifreeze liquids, in car radiators, engine cooling systems, heating circuits of car cabins.

Appearance: smooth black exterior with canvas impression, smooth black interior.

Structure: heat-resistant synthetic rubber, synthetic textile reinforcements, synthetic cover resistant to heat, aging and atmospheric agents.


Compliant with ISO 1307/1992.

Operating temperature: -40°C +120°C.

Maximum working pressure 3 bar, Burst pressure 10 bar

Minimum supply packs/lots:

- 1 meter bars
- 40 meter rolls
- 61 meter rolls



Mastertubi.it/q?353

Code	Internal diameter mm
09GRAD013/019 T	13x19
09GRAD016/022 T	16x22
09GRAD018/024 T	18x24
09GRAD020/026 T	20x26
09GRAD022/028 T	22x28
09GRAD025/032 T	25x32
09GRAD028/036 T	28x36
09GRAD030/038 T	30x38
09GRAD032/040 T	32x40
09GRAD035/043 T	35x43

09GRAD038/047 T	38x47
09GRAD040/049 T	40x49
09GRAD042/051 T	42x51
09GRAD045/054 T	45x554
09GRAD050/060 T	50x60
09GRAD055/065 T	55x65
09GRAD060/070 T	60x70
09GRAD065/076 T	65x76
09GRAD070/081 T	70x81
09GRAD080/092 T	80x92
09GRAD090/102 T	90x102
09GRAD102/113 T	102x113
09GRAD110/123 T	110x123