

GREEN FLAME-RESISTANT AIR HOSE

HOSES › Flexible pipes for ventilation or cold air extraction

Green plasticized PVC pipe, with the addition of flame-retardant additives and shock-proof rigid PVC reinforcement spiral.

The material is flame retardant according to UL 94 V0.

Perfectly smooth internal surface, corrugated external surface.

Very light and flexible.

Antistatic version with copper cord on request.

Reinforcement spiral in shockproof rigid PVC.

Temperatures of use: -10° +50°C



Mainly used in industrial ventilation and air conditioning:

- air intake
- low and medium temperature fumes
- gases produced by welding
- naval industry
- general carpentry



Mastertubi.it/q?1312

Diameter mm	Weight g/m	Vacuum packed m H ₂ O	Rolls m
25	160	2.0	50
32	200	2.0	50
38	250	2.0	50
40	280	2.0	50
45	350	2.0	50
50	430	2.0	50
52	440	2.0	50
55	470	2.0	50
60	510	1.6	50
63	540	1.6	50
70	580	1.5	50
76	630	1.5	50
80	750	1.5	50
90	840	1.5	30
100	980	1.3	30
102	1000	1.3	30
110	1090	1,2	30
120	1190	1.0	30

127	1260	0.9	30
130	1280	0.9	30
140	1450	0.9	30
152	1610	0.9	20
160	2200	0.9	20
180	2510	0.9	20
200	2940	0.9	20
203	2990	0.9	20
250	3590	0.9	10
254	3640	0.9	10
300	4440	0.9	10

For quantities and packs on request.