

## ANTISTATIC FOOD VENT PU/Z HOSE

HOSES › Food grade hoses for abrasive fluids

Ether-based polyurethane hose and food-grade rigid PVC spiral. Completely smooth internally. excellent resistance to abrasion, microbial attacks and hydrolysis; free from phthalates and other plasticizers. High mechanical characteristics, very light and flexible, notable resistance to abrasion and bending. Resists many chemicals. If the tube is equipped with a copper cord it becomes electrically conductive when it is earthed.



Mastertubi.it/q?955

Food grade according to FDA REG. Cf. 21-Item 17.2600 (aqueous and fatty foods) and EU Reg. 10/2011, classes A, B, C, D2 and dry foods)

### The spiral is also food grade

Operating temperature: -40°C to +80°C

### FIELDS OF APPLICATION:

for suction of liquid and dry foods such as flours, feed, grains of different sizes, highly abrasive products such as sugar, salt and dried fruit.

Dimensions mm	thickness minimum wall	Weight g/m	Depression mH2O	Radius of curvature mm	Rolls m
30	1.2	320	9	130	30
32	1.2	350	9	140	30
35	1.3	380	9	160	30
38	1.3	420	9	180	30
40	1.5	500	9	190	30
45	1.5	570	8	200	30

50.8	1.5	700	8	215	30
55	1.5	780	8	225	30
60	1.5	870	8	230	30
63.5	1.5	920	8	240	30
65	1.5	940	8	240	30
70	1.5	950	7	240	30
76.2	1.7	1120	7	270	30
80	2.0	1260	7	290	30
90	2.0	1410	7	380	30
100	2.0	1600	7	420	30
102	2.0	1630	6.5	420	30
110	2.0	2220	6.5	450	30
120	2.0	2410	6.5	480	30
127	2.0	2540	6.5	530	30
152	2.0	3110	6	800	20