

# **PURE AQUA TUBE**

HOSES > Hoses for food products

#### **TECHNICAL DESCRIPTION**

Special polymer tube, compliant with ACS standards, for the transfer of drinking water, white, smooth.

Reinforcement in synthetic fabric with incorporated steel spiral for internal diameters =32 mm Special polymer coating, resistant to oils and atmospheric agents, blue, canvas effect. Operating temperature  $-20^{\circ}\text{C} => +100^{\circ}\text{C}$ .

Special properties Maximum vacuum: 0.9 bar from 32 to 100 mm diameter.

### **APPLICATIONS**

Suitable for a wide range of uses, including the transfer of drinking water in the beverage industry, mobile food service units and commercial kitchens.

It is also suitable for temporary or emergency installations such as campsites, caravan parks, outdoor events, public festivals and operations in hospitals, airports or municipal services. High-quality rubber hose designed for transporting drinking water. Its special compound ensures odorless and tasteless transfer without altering the water's original characteristics.





#### **ADVANTAGES**

- Highly flexible, very easy to handle.
- A smooth, seamless, white pipe, suitable for transporting drinking water and offering high performance that does not promote bacte growth.
- Excellent bending resistance for versions equipped with steel spiral.
- Resistant to cleaning with the most common detergents (see our cleaning instructions for details) or with steam at a maximum temperature of 130°C.
- Non-marking and abrasion-resistant coating. Contains no phthalates.

### **TECHNICAL DESCRIPTION**

Underlayer made of special polymer, compliant with ACS regulations for the transfer of drinking water, white, smooth.

Synthetic textile reinforcement with embedded steel spiral for internal diameters =32 mm

Special polymer coating, resistant to oils and weathering, blue, canvas effect.

Operating temperature -20°C => +100°C.

Special properties Maximum vacuum: 0.9 bar from 32 to 100 mm diameter.

## REFERENCE REGULATION, APPROVAL

- · Hose compliant with the French ACS (Attestation de Conformité Sanitaire) regulation for drinking water.
- FDA Regulation No. 21 CFR 177.2600.

All relevant migration tests were performed by an external laboratory authorized by the Ministry of Health and confirmed.

Diameter internal mm	Diameter external mm	Pressure of exercise bar	Burst pressure bar	Radius of curvature mm	Weight Kg/m	Length roll m	code product
13	23	20	60	65	0.36	20	5609719
13	23	20	60	65	0.36	40	5609698
13	23	20	60	65	0.36	80	5609699
16	26	20	60	85	0.43	20	5609702
16	26	20	60	85	0.43	40	5609703
16	26	20	60	85	0.43	80	5609704
19	31	20	60	100	0.59	20	5609706
19	31	20	60	100	0.59	40	5609707
19	31	20	60	100	0.59	80	5609708
25	37	20	60	125	0.69	20	5609710
25	37	20	60	125	0.69	40	5609711
32	44	20	60	70	1.12	20	5609679
32	44	20	60	70	1.12	40	5609680
38	50	20	60	80	1.27	20	5609682
38	50	20	60	80	1.27	40	5609683
50	62	20	60	120	1.84	20	5609685
50	62	20	60	120	1.84	40	5609686
63	76	20	60	140	2.33	20	5609688
63	76	20	60	140	2.33	40	5609689
75	89.5	20	60	200	3.41	20	5609691
75	89.5	20	60	200	3.41	40	5609692
100	115.5	20	60	400	4.48	20	5609694
100	115.5	20	60	400	4.48	40	5609695