

## TRELLFLEX CHEM POLYPROPYLENE 10/14 COMPOSITE PIPE

HOSES > Chemical hoses

MULTIPURPOSE flexible hose for suction and delivery of highly corrosive **LIQUID** chemical products. **Reference** standard: EN 13765 and ADR ADVANTAGES: exceptional flexibility and manageability, use in environments subject to ATEX regulations thanks to the electrical conductivity ensured by the two steel coils. **USES:** Suction and discharge of petroleum products and derivatives with an aromatic content of up to 100% for the transfer of flammable liquids in road, railway, industrial tanker trucks and depots. Ideal for its lightness, easy handling and flexibility in manual use. Wherever chemical resistance is needed even on the surface of the pipe. **STRUCTURE:** composed of layers of **polypropylene** films compressed between two steel spirals. External covering in GRAY PVC-coated polyester canvas, wavy appearance with visible metal spiral.



- <sup>°</sup> 10 bar operating pressure
- <sup>°</sup> 14 bar operating pressure
- Internal and external spiral in galvanized/GALVANIZED steel coated with polypropylene (PG)
- Internal and external spiral in AISI 316 stainless steel
  (SS)

## PERFORMANCE:

Maximum suction 0.9 bar (approximately empty).

Operating temperature: -30° +100° C.

Maximum operating pressure 10/14 bar depending on the versions

- Burst pressures 40/56 bar. Supplied exclusively in lengths of use with fittings











assembled in: aluminium, brass, polypropylene, stainless steel.

Possibility of having fitted fittings such as: male, female, Cam-lock, Guillemin, Rapid, fixed/revolving flanges ISO PN10/16, ASA 150.

## HYDROSTATIC TEST CERTIFICATE AND ELECTRICAL CONDUCTIVITY CERTIFICATE ATTACHED UPON REQUEST.

| Dimension<br>mm | radius<br>of curvature<br>mm | Weight kg/m | Length<br>maximum<br>m |
|-----------------|------------------------------|-------------|------------------------|
| 25x37           | 100                          | 0.84        | 30                     |
| 32x43           | 120                          | 1.03        | 30                     |
| 40x52           | 140                          | 1.26        | 30                     |
| 50x62           | 180                          | 1.97        | 30                     |
| 65x78.5         | 200                          | 2.82        | 30                     |
| 80x95           | 280                          | 3.30        | 30                     |
| 100x121         | 400                          | 3.96        | 20                     |
| 125x149         | 450                          | 8.16        | 15                     |
| 150x180         | 500                          | 10.80       | 20                     |
| 200x234         | 740                          | 5.60pm      | 20                     |
| 250x297         | 920                          | 10.50pm     | 12                     |