

HEAT PIPE/10/SPL MULTIPURPOSE

HOSES › Chemical hoses

Smooth black rubber hose with embedded steel spiral. Suitable for suction and delivery of hot and sea water.

Construction: Heat-resistant EPDM synthetic rubber, synthetic textile reinforcements, aging- and weather-resistant EPDM synthetic cover. Embedded steel spiral.

Appearance: Smooth black canvas impression exterior, smooth black interior.

Use: Pipe suitable for the passage of hot water, even mixed with steam, and antifreeze liquids, in car radiators, engine cooling systems, heating circuits of vehicle cabins, chemicals, and sea water.

Working temperature: -40°C +120°C.

Maximum continuous working pressure: 10 bar - safety factor 3

Packaging: Rolls of 20/40/60 meters DEPENDING ON THE DIAMETERS

On request for some diameters also in super-flexible FLEX version for bending radii.



Mastertubi.it/q?694

item	OR mm	radius of curvature mm	RC FLEX mm	aspiration bar
09GCAL013/023SP	13x23	80	-	0.9
09GCAL016/026SP	16x26	90	70	0.9
09GCAL018/028SP	18x28	110	75	0.9
09GCAL019/029SP	19x29	115	-	0.9
09GCAL020/030SP	20x30	120	80	0.9
09GCAL025/035SP	25x35	150	100	0.9
09GCAL030/040SP	30x40	180	120	0.9
09GCAL032/043SP	32x43	190	130	0.9
09GCAL035/046SP	35x46	210	140	0.9
09GCAL038/049SP	38x49	230	150	0.9
09GCAL040/051SP	40x51	240	160	0.9
09GCAL045/057SP	45x57	270	180	0.9

09GCAL051/063SP	51x63	310	200	0.9
09GCAL060/071SP	60x71	360	240	0.9
09GCAL063/076SP	63x76	380	270	0.9
09GCAL070/082SP	70x82	420	280	0.9
09GCAL076/088SP	76x88	460	300	0.9
09GCAL080/092SP	80x92	480	320	0.9
09GCAL090/102SP	90x102	540	340	0.9
09GCAL102/117SP	102x117	610	400	0.9
09GCAL110/123SP	110x123	660	-	0.9
09GCAL120/137SP	120x137	720	680	0.9
09GCAL127/144SP	127x144	760	760	0.9
09GCAL152/170SP	152x170	920	920	0.8
09GCAL203/228SP	203x228	1220	-	0.7
09GCAL254/280SP	254x280	1524	-	0.7
09GCAL305/331SP	305x331	2100	-	0.5