

FEMALE-FEMALE LEVER BALL VALVE NPT THREAD

BALL VALVES - GATE VALVES › LOW PRESSURE BRASS BALL VALVES

Ball valve for every hydraulic and pneumatic system.

Ideal for water, oils, compressed air.

Operating temperature: -20° +150°C in the absence of steam

Female-Female NPT threaded connection



Description:

nut: galvanized steel

lever handle in galvanized Fe P04 steel, covered in red PVC

OR-NBR 70 SH/A gasket

OT CW 614 N nickel-plated operating rod - UNI EN 12165/98

OT CW617 N nickel-plated sleeve

sphere in thick chromed OT CW617N

virgin PTFE seal

body in nickel-plated OT CW617N - UNI EN 12165/98

VITON rod seal



Mastertubi.it/q?1169

Code	Dimensions mm	Pressure bar	Packaging box
510050N001/4	1/4"	40	12
510050N003/8	3/8"	40	12
510050N001/2	1/2"	40	12
510050N003/4	3/4"	40	8
510050N1	1"	40	8
510050N1_1/4	1"-1/4	32	4
510050N1_1/2	1"-1/2	32	2
510050N2	2"	32	2
510050N2_1/2	2"-1/2	32	1
510050N3	3"	32	1
510050N4	4"	32	1

