

Antistatic SUPERFLEX PVC SEWAGE HOSE

HOSES › Water intake hoses

PVC/NBR hose for medium suction and transfer of water, liquid fertilizers, septic tank purging. Wavy external surface with shock-proof rigid PVC spiral.

On request in ANTISTATIC version.

Excellent for aspirations in general, particularly on tankers where it guarantees excellent flexibility and softness even at low temperatures.



Item number	Dimension Ø mm	Weight gr	Operating pressure bar	Burst pressure bar	depression bar	Curvature radius m	Rolls m
04APOLLO0052SPF	50.8	1000	2	10	0.7	160	50
04APOLLO0063SPF	63.5	1400	1.8	9	0.7	210	50
04APOLLO0076SPF	76.2	1700	1.8	9	0.7	250	50
04APOLLO0080SPF	80	1850	1.5	7.5	0.7	270	50
04APOLLO0090SPF	90	2150	1.5	7.5	0.7	300	30
04APOLLO0102SPF	102	2700	1.3	6.5	0.6	335	30
04APOLLO0110SPF	110	3000	1,2	6.0	0.6	360	30
04APOLLO0127SPF	127	3600	1.1	5.5	0.6	410	30
04APOLLO0152SPF	152.4	5000	0.9	4.5	0.6	500	20