

ASPIROIL/10 HOSE

HOSES › Hydrocarbon suction hoses

Hose for suction and delivery of fuels, oils and lubricants, diesel with aromatic content up to 50%. Smooth black NBR rubber tube, with textile reinforcement, steel spiral and incorporated copper cables for earthing.



Black NBR rubber cover with cloth finish, resistant to hydrocarbons, atmospheric agents and ozone.

Operating temperature: -30° +80° C

40-61 meter rolls

Operating pressure 10 bar, burst pressure 30 bar

Maximum depression value 0.9 bar



Mastertubi.it/q?287

Also available in the version with conductive underlayer

$R < 10^{-6} \text{ } \Omega/\text{m}$

Code item	Dimension OR mm	radius Of curvature mm
06GBAS0000020 T	19x29	115
06GBAS0000025 T	25x35	150
06GBAS0000030 T	30x40	180
06GBAS0500032 T	32x42	190
06GBAS0000035 T	35x45	210
06GBAS0000038 T	38x49	240
06GBAS0000040 T	40x51	240
06GBAS0000042 T	42x53	255
06GBAS0000045 T	45x56	270
06GBAS0000050 T	50x62	300

06GBAS0000060 T	60x72	360
06GBAS0000063 T	63x76	380
06GBAS0000070 T	70x83	400
06GBAS0000075 T	76x89	460
06GBAS0000080 T	80x94	480
06GBAS0000090 T	90x104	540
06GBAS0000100 T	102x118	600
06GBAS0000100 T	102x118	600
06GBAS0000120 T	120x135	720
06GBAS0000127 T	127x143	760
06GBAS0000152 T	152x170	900