

STAINLESS STEEL BRAIDED SMOOTH TEFLON-PTFE HOSE

HOSES › Chemical hoses


Injection extruded sintered PTFE tube, resistant to all chemical agents and non-toxic, food grade compound. Excellent resistance to chemicals, flame, heat, excellent dielectric and fireproof properties, unchanged in contact with ozone and ultra-violet rays.

Operating temperature: -70° +260° C.

Tolerances according to BS EN ISO 13000-1:1998

Standard version smooth tube with AISI 304 stainless steel external braid.

Other versions with the possibility of inserting textile braids: in fiberglass or terylene or Nomex or with INOX braid
On request also in the version with black ANTISTATIC underlayer which can be used in ATEX areas.



Mastertubi.it/q?302

Diameters inch	Diameters mm	Weight g/m	Pressure of work Cafe	Pressure of explosion Cafe	radius of curvature mm
1/8"	3.2x5.9	60	270	1080	25
3/16"	4.8x7.4	69	200	800	35
1/4"	6.35x9	87	175	700	45
5/16"	7.9x10.8	127	150	600	50
3/8"	9.5x12.4	145	135	540	60
13/32"	10.3x13.3	158	130	520	70
1/2"	12.7x15.7	212	120	480	90
5/8"	15.9x19.1	260	100	400	120
3/4"	19x22.2	321	90	360	190
7/8"	22.2x25.6	355	70	280	250
1"	25.4x29.3	450	65	260	270