

M240/SC - E/24-SC MODULAR FILTER-PRESSURE REGULATOR WITH AUTOMATIC CONDENSATE DRAIN

FITTINGS FOR COMPRESSED AIR › COMPONENTS FOR INDUSTRIAL COMPRESSED AIR PLANTS › AIR TREATMENT GROUPS FOR PLANTS

M 240 - E/24	M 240/P - E/24-P
Modular pressure regulator filter with technopolymer glass	Modular pressure regulator filter with metal cup
M 240/SC - E/24/SC	M 240/SC/P - E/24/SC-P
Modular pressure regulator filter with technopolymer glass and automatic drain device	Modular pressure regulator filter with metal cup and automatic drain device



These Filter-Regulators combine the function of pressure regulator and filtering unit in a single unit. They have been designed to remove liquid and solid impurities in pneumatic systems. They are modular filters equipped with a **PE filter cartridge** that retains impurities with dimensions greater than **40 µ**. On request you can have different degrees of filtration **5 µ** or **20 µ**. The characteristic of being modular allows you to assemble multiple elements of the same family with different functions in a single block.

Connections:

- **1/2" BSP** Threads on body
- **3/8" BSP** With reduction

General characteristics

- Powder coated metal body.
- Cup with quick coupling in technopolymer (**E/24 series**) or metal (**E/24-P series**) with a capacity of **50 cm³**.
- Semi-automatic and manual unloading device upon request.

Complete with connection for drainage pipe connection.
(Automatic unloading device only for model **E/24/SC**)

- Deflector and air conveyor for effective condensation separation.
- Piston pressure regulation system
- Overpressure relief valve, relieving function, standard.
- Adjustment knob equipped with locking system and technopolymer fixing ring nut
- All models include the supply of a square pressure gauge with **a 0/16 bar - 0/230 psi scale**



Mastertubi.it/q?31